

Medallion Plus[®] Motor Oils

PRODUCT DESCRIPTION

Medallion Plus[®] Motor Oils are energy-conserving oils containing the highest quality base stocks and performance additives. These products possess excellent low temperature fluidity and will provide outstanding protection against wear, sludge and corrosion under the most severe operating temperatures.

Medallion Plus Motor Oils are offered in SAE viscosity grades 5W20, 5W30 and 10W30. MP 5W20 is generally intended for Honda and Ford engines that call for SAE 5W20 engine oil. MP 5W30 is common in all other new engines for its energy saving characteristics. MP 10W30 is suitable for older engines, or any engine operating in sustained high temperature environments.

INDUSTRY APPROVALS

Medallion Plus[®] Motor Oils meets the specifications of:

- API SM/SL/SJ/SH
- ILSAC GF-4
- GM 6094M
- Ford WSS-M2C930-A
- Ford WSS-M2C929A
- Chrysler MC6395

TYPICAL ANALYSIS

Property	ASTM Method	5W20	5W30	10W30
Viscosity @ 100 °C, cSt	D445	8.7	10.5	10.3
Color	D1500	2.5	2.5	2.5
Viscosity Index	D2270	150	153	140
6600 cP max at C Deg.	D2602	-35	-35	-30
Pour Point (min) C	D97	-39	-39	-35
Flash Point °F	D92	400	400	400
Gravity, API @ 60 F	D287	33	33	31

HEALTH & SAFETY

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your Customer Service Center. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment. Due to continual product research and development, the information contained herein is subject to change without notification.

